



Jet-Air
Cool, Warm & Collected

- I-FEEL function
- Smart zone controller
- Power-off memory function
- Low-temperature cooling function (optional)

Ducted Split



Proudly distributed by

JASA
Smart Home

Johannesburg (011)708 1148
Pretoria (012)752 8777
East Rand (011)823 2119
Cape Town (021)823 8866

Durban (031)577 0498
Nelspruit (013)752 3258
Port Elizabeth (041)364 0947
Botswana (00267)262 2909





Ducted Split Type Technical Specifications



- I-FEEL function
- Power-off memory function
- Smart zone controller
- Low-temperature cooling function (optional)

Model	Indoor		JASA-HI-H24A4/FI	JASA-HI-H36A4/FI	JASA-HI-H36A5/FI	JASA-HI-H48A4/FI	JASA-HI-H48A5/FI	JASA-HI-H60A5/FI
	Outdoor		JASA-H24A4/FIU	JASA-H36A4/FIU	JASA-H36A5/FIU	JASA-H48A4/FIU	JASA-H48A5/FIU	JASA-H60A5/FIU
Power Supply		V~, Hz, Ph	220~240, 50, 1	220~240, 50, 1	380~415, 50, 3	220~240, 50, 1	380~415, 50, 3	380~415, 50, 3
Capacity	Cooling	Btu/h	23884	34120	34120	47768	47768	54592
		kW	7.00	10.00	10.00	14.00	14.00	16.00
	Heating	Btu/h	27296	40944	40944	52886	52886	56298
		kW	8.00	12.00	12.00	15.50	15.50	17.00
Electric Data	Rated Cooling Power Input	kW	2.18	3.20	3.12	4.70	5.10	5.60
	Rated Heating Power Input	kW	2.21	3.40	3.32	4.40	4.50	4.57
	Rated Cooling Current	A	10.10	15.00	5.40	21.80	8.80	9.70
	Rated Heating Current	A	10.20	15.50	5.80	20.40	7.80	7.90
Performance	EER/COP	W/W	3,21/3,62	3,12/3,53	3,21/3,61	2,98/3,52	2,75/3,44	2,86/3,61
	Indoor Air Flow	m ³ /h	1400	2100	2100	2400	2400	3000
Indoor Unit	Noise Level(Hi/Mi/Lo)	dB(A)	46/44/40	52/48/44	52/48/44	53/49/45	53/49/45	56/54/49
	External Static Pressure	Pa	0-75	0-100	0-100	0-125	0-125	0-150
	Net Dimension (W*H*D)	mm	1279*558*268	1226*775*290	1226*775*290	1340*750*350	1340*750*350	1340*750*350
	Packing Dimension (W*H*D)	mm	1348*597*283	1338*877*305	1338*877*305	1423*837*455	1423*837*455	1423*837*455
	Net/Gross Weight	Kg	34.0/39.0	46.0/53.0	46.0/53.0	57.0/69.0	57.0/69.0	57.0/69.0
	Noise Level	dB(A)	57	63	63	59	59	63
Outdoor Unit	Dimension (W*D*H)	mm	980*427*790	1107*440*1100	1107*440*1100	958*412*1349	958*412*1349	1085*427*1365
	Packing	mm	1083*488*855	1158*493*1235	1158*493*1235	1043*453*1500	1043*453*1500	1143*478*1505
	Weight	kg	67/72	92/100	98/106	105/115	114/124	126/138
Refrigerant Pipe	Liquid Side	inch	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
	Gas Side	inch	5/8"	5/8"	5/8"	5/8"	5/8"	3/4"
	Max. Length	m	30	30	30	50	50	50
	Max. Height	m	15	15	15	30	30	30



12-24K



36K



48-60K

Due to JASA policy of constant improvement, specifications are subject to change without prior notice.

Remarks: Cooling capacities are based on indoor air temp. 27°C DB, 19°C WB and outdoor air temp. 35°C DB, 24°C WB. The above specifications are subject to change without prior notice for product improvement.

E.A.O.E.

www.jet-air.co.za

Remark: The above designs and specifications are subject to change of product improvement without prior notice.

